

LIGHT RAMP

NOTE: The audible and acoustic signals should include the following components:

1. Control unit for flashing light and siren - 1 unit / motor vehicle
2. Front flashers (red/blue), led controller - 4 pcs / motor vehicle
3. Back flashers (red/blue) – 4 pcs / motor vehicle
4. Light ramp as per minimum specifications below - 1 unit / motor vehicle:

Color	Blue/Red	
LED light ramp	LED, Radiator aluminum	Min 60 LEDs, magnifying lens
360 degree light	Yes	
Light sensor	Yes	Automatic/manual brightness change
Illumination regimes	25	Operator choice
Traffic routing	-	
Number of LEDs, Flasher on the left	30 LED	With magnifying lens
Number of LEDs, Flasher on the right	30 LED	With magnifying lens
Number of LEDs, Siren flasher	3+3 LED	With magnifying lens, stationary
LED power, one led/ total flasher, Watt	3 Watt/198 Watt	With magnifying lens
Directional reflector	Yes	For every LED
Left LED light	Yes, 6 LED	18 Watt, with magnifying lens
Right LED light	Yes, 6 LED	18 Watt, with magnifying lens
Single control system, light ramp	Yes	With operating mode indication, color display
Length, LED light ramp, m	1.165	
Width, LED light ramp, m	0.36	
Height, LED light ramp, m	0,069/0,084	
Siren device	Yes, located in center	6 sounds, Wail, Yelp, Hilo, Manual, Combined i Horn
Beep frequency, siren device		300 – 10000 Hz
Beep power, siren device		100 Watt, 120-127 dB
Single control system, siren	Yes	With microphone, color display
SOS system	Yes	All signals switched on in case of emergency
Backup power line	Yes	
Warranty	24 months	