Annex No. 3 – Police Light Ramp

NOTE: The sound and acoustic signals must include the following components:

- 1. Control unit for flashing light and siren 1 unit / motor vehicle
- 2. Front flashers (red/blue), led controller 4 pcs / motor vehicle
- 3. Back flashers (red/blue) 4 pcs / motor vehicle
- 4. Light ramp as per minimum specifications below 1 unit / motor vehicle

Colour	Blue/Red	
LED Lightbar	LED, Aluminum Radiator	Min 60 LED Lens
360-Degree Light	Yes	
Light Sensor	Yes	Automatic or Manual Brightness Adjustment
Lighting Modes	25	selectable by operator
Traffic Routing	-	
LED quantity, Left Beacon	30 LED	LED lens
LED quantity, Right beacon	30 LED	LED lens
LED quantity, siren Beacon	3+3 LED	LED lens, stationary mode
LED Power, one LED unit/ total per lightbar, Watt	3 Watt/198 Watt	LED Lens
Directional Reflector	Yes	For each LED
Left LED Light	Yes, 6 LED	18 Watt, LED lens
Right LED Light	Yes, 6 LED	18 Watt, LED lens
Lightbar Single Control System,	Yes	Working mode indicator, color display
Lightbar Length (m)	1.165	
Lightbar Width (m)	0.36	
Lightbar Height (m)	0,069/0,084	
Siren Device	Yes, centrally located	6 sounds, Wail, Yelp, Hilo, Manual, Combined, Horn
Siren Frequency		300 – 10000 Hz
Siren Power		100 Watt, 120-127 dB
Single Control System, Siren	Yes	with microphone, Color Display
SOS System	Yes	All signals activated in case of emergencie
Backup Power Line	Yes	
Warranty	24 months	