

Table 1: Technical Specifications

No	Generic description / Components	Total quantity
MRZ scanners for biometric passports		300
1.	Type of operation: stationary Connectivity interface: USB 1.1 to USB 3.0 (wired) Bar code recognition: <ul style="list-style-type: none"> • machine readable passports (MRP) – 2 lines composed of 44 characters • travel documents – 2 lines composed of 36 characters / 3 lines composed of 30 characters • OCR ticket data – data printed in accordance with IATA Recommended Practice 1720a, including ATB-1 type 407-E, 1403M, OCRB, OCRA and IATA 2 of 5 barcode data • standards: ICAO 9303 and e-passports Standard OCR fonts: OCR-B and E13B Dimensions (max. L x W x H): 220 x 60 x 60 mm Cable length: 1500 mm (min.) to 2700 mm (max.) Weight: max. 650 g Operation temperature range: 0°C to +50 °C Input voltage: +5 V Security rating: UL 1950 / IEC950 Impact resistance: at least 50 cm Feedback indicators: LED and/or audio	300 units
2.	Warranty: (minimum) 24 months	
Total quantity		300 units

Table 2: Delivery Schedule

Item #	Support required	Timeframe
1.	Delivery of the MRZ scanners for biometric passports to the CEC	15 September 20209 (not later than)
3.	Remote support performed by qualified technicians <i>(in Romanian language)</i>	As required during the warranty period.